



## 2011 TOUR

**A-A** 38" +/- .125"  
**String** 58 5/8"

**Brace** 7 7/8" +/- .125"  
**Cable** 41 15/16"

<b>Tour Cam TR Mod</b>	<b>Cam setting @ Brace from .160 hole to inside of limb</b>	<b>Speed Rating #70 350 grain arrow</b>
#5 – 30"	1.23" gap	305-308 fps
#6 – 29.5"	1.20" gap	300-303 fps
#7 – 29"	1.21" gap	295-298 fps
#8 – 28.5"	1.215" gap	290-293 fps
#9 – 28"	1.185" gap	285-288 fps
#10 – 27.5"	1.160" gap	280-283 fps
#11 – 27"	1.130" gap	275-278 fps

**Deduct 2-3 fps from rating for #60 peak weight**

<b>Limb Deflection</b>	<b>Poundage of Bow</b>	<b>Pivots</b>
90	70	Tall
114	60	Tall
210	50	Tall
<b>Speed Buttons</b>	<b>Qty</b>	<b>Location</b>
Custom Elite	2	1 <sup>st</sup> one 4" from axle
<b>Spacers</b>	.060" string side	.070" cable side +/- .005"
<b>Cable Rod</b>	7 1/2"	<b>Suppressor Rod w/ Bends</b> 5 3/4"